



The perfect choice for a variety of industrial and commercial projects. The Xtra range of rugged and tough surface metalclad accessories are produced from high quality steel with an epoxy powder coating for corrosion resistance.

## 7.1

### SWITCHES

10A switches .....	65
3 Pole isolator switches .....	65
10A broad rocker switches .....	65
20A/50A double pole switches .....	65

## 7.2

### SOCKET OUTLETS

13A unswitched sockets .....	66
13A double pole switched sockets inboard rockers .....	66
13A 2G double pole switched sockets outboard rockers .....	66
13A 1G/2G double pole non-standard/clean earth switched sockets .....	66
13A RCD socket .....	66
5A/15A sockets .....	67
13A lockable outlet .....	67

## 7.3

### FUSED CONNECTION UNITS

13A fused connection units – unswitched .....	68
13A fused connection units – switched .....	68
13A fused connection units with red rockers/fuse drawers with optional cable outlets .....	68

## 7.4

### PREMERA MIX MODULE PLATES AND BLANK PLATES

Modular plates/grids .....	69
Blank plates .....	69

X022MG



### 10A switches

- To BSEN 60669-1.
- Supplied with M3.5 fixing screws. Each terminal is capable of accepting up to 3 x 1.5mm<sup>2</sup> conductors. All terminals are backed off, ready to accept cable. X-rated for fluorescent or inductive loads.

Description	Eaton list number
10A 1G 2 way	<b>X021MG</b>
10A 2G 2 way	<b>X022MG</b>
10A 3G 2 way	<b>X023MG</b>
10A 1G intermediate	<b>X017MG</b>

X048MG



### 3 pole isolator switches

- To BSEN 60669-1.
- Supplied with M3.5 fixing screws. Each terminal is capable of accepting up to 3 x 1.5mm<sup>2</sup> conductors. All terminals are backed off, ready to accept cable. X-rated for fluorescent or inductive loads.

Description	Eaton list number
10A broad fan isolator + fan symbol	<b>X048MG</b>
10A broad fan isolator	<b>X049MG</b>

X401NMG



### 20A double pole switches

- To BSEN 60669-1.
- Supply terminals accept 3 x 2.5mm<sup>2</sup> conductors. Load terminals accept 2 x 2.5mm<sup>2</sup> conductors.

Description	Eaton list number
20A DP switch	<b>X401MG</b>
20A DP switch + neon	<b>X401NMG</b>

### 50A double pole switch

- To BSEN 60669-1.

Description	Eaton list number
50A DP switch + neon (2 gang size)	<b>X421NMG</b>

X111MG

**13A unswitched socket outlets**

- To BS 1363:Part 2.
- Terminals capable of accepting up to 3 x 4mm<sup>2</sup> or 2 x 6mm<sup>2</sup> conductors.

Description	Eaton list number
13A 1G unswitched socket	<b>X111MG</b>
13A 2G unswitched socket	<b>X112MG</b>

X621MG

**13A double pole switched sockets**

- To BS 1363: Part 2.
- 2 earth terminals and inboard rockers.

Description	Eaton list number
13A 1G DP switched socket with 2E terminals	<b>X621MG</b>
13A 1G DP switched socket with 2E terminals + neon	<b>X621NMG</b>
13A 1G DP switched socket with 2E terminals + red rocker	<b>X621RRMG</b>
13A 2G DP switched socket with 2E terminals	<b>X622MG</b>
13A 2G DP switched socket with 2E terminals + neon	<b>X622NMG</b>
13A 2G DP switched socket with 2E terminals + red rocker	<b>X622RRMG</b>

X632MG

**13A 2G double pole switched sockets outboard rockers**

- To BS 1363: Part 2.
- Terminals capable of accepting up to 3 x 4mm<sup>2</sup> or 2 x 6mm<sup>2</sup> conductors.
- 2 earth terminals and outboard rockers.

Description	Eaton list number
13A 2G DP switched socket with 2E terminals	<b>X632MG</b>
13A 2G DP switched socket with 2E terminals + red rockers	<b>X632RRMG</b>

X651MG

**13A 1G double pole non-standard/clean earth switched sockets**

- Non-standard socket interface to BS 5733 with clean earth facility.

Description	Eaton list number
13A 1G DP switched socket	<b>X651MG</b>
Non-standard plug top	<b>F3368</b>

X652MG

**13A 2G double pole non-standard/clean earth switched sockets**

- Non-standard socket interface to BS 5733 with clean earth facility.
- Outboard rockers.

Description	Eaton list number
13A 2G DP switched socket with 2E terminals	<b>X652MG</b>

X686MG

**13A double pole RCD socket outlet – passive**

- To BS 7288.
- Added protection against electrocution.
- Passive – the contacts on the passive device remain closed when the mains supply is interrupted – this type is suitable for applications such as fridge freezers etc.

Description	Eaton list number
13A 2G RCD protected socket passive 30mA	<b>X686MG</b>

X105MG



### 13A lockable socket

- To BS 1363 Part 2.

**Description**

13A 1G socket 2G plate size with common key

**Eaton list number**

**X105MG**

X305MG



### 5A socket outlet

- To BS 546.

**Description**

5A 1G unswitched socket

**Eaton list number**

**X305MG**

X415MG



### 15A socket outlet

- To BS 546.

**Description**

15A 1G switched socket

**Eaton list number**

**X415MG**